

PCM4-H77 - Marine Computer



Removable Drive Option:



PCM4-H77 enables the new Ivy Core i3, Core i5 and Core i7 Intel CPU for marine and naval mission critical applications.

PCM4- H77 is tested for full compliance to IACS E10, IEC60945, EN61000-6-2 and EN61000-6-4 and holds certificates from major class societies.

The PCM4 cabinet allows for flexible installation, bolted to a surface using the mounting-angles, and/or mounted in a 19" rack using the optional "rack-ears".

The **PCM4- H77** features a new 5½" Option that combines a Removable Solid State Drive and a Slide-in DVD drive.

- Thermal and mechanical designed cabinet.
- State-of the-art Computer technology.
- Intel H77 Chipset
- Ivy Core i3, i5 and i7 Intel CPU
- Intel HD Graphics
- Rugged and compact design.
- Vibration-proof hard disk drive.
- High grade low noise fan.
- Compliance with IEC60945 ed. 4 and IACS E10 rev. 5
- Holds major type-approval certificates.



Specifications

PCM4-H77 - General

CPU: Core™ i3-3220 (2 Cores, 4 Threads)

Optional Core[™] i5-3550S (4C/4T) Optional Core[™] i7-3770 (4C/8T)

Chipset: Intel® H77 Express

64Bits, Hyper-Threading and Virtualization Technology with Enhanced

SpeedStep® and Turbo Boost Technology

5GT/s Direct Media Interface

Memory: 1 GB DDR3 RAM 1066 MHz (Standard)

Optional Upgrades

4 DIMM sockets supporting up to a total of 16GB DDR3 1066/1333/1600 RAM

Video: On-CPU Intel HD Graphics 2500 (Core i3/i5) / 4000 (Core i7)

The maximum supported resolution is 1900 x 1200 (WUXGA)

DirectX 10.1 and OpenGL 3.0 compliant DirectX 11.0 CS4.0 only / Shader model 4.0

Dual independent display support Optional PCIe x16 graphics card

Audio: 10-channel (7.1 + 2) Intel High Definition Audio (Realtek ALC892 audio

Codec)

Ethernet: 10/100/1000 Mbit/sec Ethernet (RJ45) - onboard

Hard Disk Drive: 100+GB 2.5", SATA (Standard)

Optional Upgrades

Sizes up till 500GB, 24/7 rated disk, 2.5" SATA

Solid State Disc 32,64,128 GB

51/4" drive bay: DVD-R/W Drive (SATA interface)

Optional Combined Removable Solid State disk drive and Slide-in DVD drive

PCM4-H77 - Ports

Video: HDMI+DVI-I + DisplayPort video out

Audio: 5x 3.5mm jack socket, Optical S/PDIF out

Ethernet: 1x RJ45

Serial: Optional 1 x RS232 un-isolated. Routed to back from Motherboard header.

USB: 4x USB 3.0 ports (2 on back and 2 on internal header)

10x USB 2.0 ports (4 on back, 2 on internal header, 2 via Mini PCle and 2

accessible from front)

SATA: RAID 0,1,5,10 supported by onboard Intel Rapid Storage Technology

2x 6.0Gb/s, 3x 3.0Gb/s (1 port shared with mSATA on Mini PCle)

eSATA: 1x eSATA 3.0Gb/s (on back)

Expansion Slots: 1x PCI Express x16, 1x PCI Express x4, 1x PCI Express x1, 3x PCI

1x PCI Express Full-/Half-Mini Card slot with support for mSATA

PCM4-H77 - Power

Standard: 90-264 VAC, 50-60 Hz, 300 Watt

Automotive: 18-36 VDC

PCM4-H77 - Environmental

Operating Temperature: -15 to 55 °C Storage Temperature: -25 to 70 °C Relative Humidity: 8 to 90 %

PCM4-H77 - Approvals

CE Mark: EN61000-6-2 & EN61000-6-4

Marine: IACS E10 rev. 5 & IEC 60945 Ed. 4

Type Approvals: DNV

For latest marine class approvals - see www.isic-systems.com

PCM4-H77 - Dimensions

Basic Version: 420 x 132 (3U) x 380 mm

Brackets: Mounting-angles - Optional 19" brackets for 19" rack-mount (on shelf)

Weight: 11 Kg